

Cascade *Product Specifications*



High Capacity Carbon Block Filtration System

Specifications	Model CAS-1	Model CAS-2	CAS- 1 - UV
Filter type No 1 (Sediment)	25 micron Spun Polypropylene	25 micron Spun Polypropylene	25 micron Spun Polypropylene
Filter Type No 2 (Carbon)	Block carbon – 10 micron	GAC carbon	Block carbon – 10 micron
Filter Type No 3 (Carbon)	Block carbon – 10 micron	Block carbon – 10 micron	Block carbon – 10 micron
Capacity *	1700 gallons	1700 gallons	1700 gallons
Flow Rate *	.5 Gallons per minute	.5 Gallons per minute	.5 Gallons per minute
Max Operating Pressure	100 psi	100 psi	100 psi
Recovery	N/A	N/A	N/A
Electrical	N/A	N/A	24 VAC
Maximum Feed Temperature	122 F (50 C)	122 F (50 C)	122 F (50 C)
Systems Dimensions	17" x 15" x 18" 33 cm x 35.5 cm x 43 cm	17" x 15" x 18" 33 cm x 35.5 cm x 43 cm	17" x 15" x 18" 33 cm x 35.5 cm x 43 cm
Weight lbs. (kg)	8 lbs (3.64)	8 lbs (3.64)	8 lbs (3.64)

** Capacity and flow rate are based on .5 gallon per minute flow out of faucet. U.V. rating is also .5 gallon per minute with rated lamp life of 8,000 hours. Transformers available for 100 V, 115 V and 230 Volt electrical.*

Nimbus Water International, Sea Lion Place, Suite 103, Carlsbad, CA 92008 USA

Website: www.nimbuswaterintl.com
Phone: 760.603.0867
Fax: 760.603.0868
Email: salesinfo@nimbuswaterintl.com