

# Ton Series *Product Specifications*

---



## **High Capacity Filtration Cartridges**

<b>Specifications</b>	<b>Model TON</b>	<b>Model TOSN</b>
<b>Filter type</b>	Molded Carbon Block	Molded Carbon Block/Polyphosphate
<b>Filter body</b>	Polypropylene	Polypropylene
<b>Micron Rating</b>	1 Micron Nominal	1 Micron Nominal
<b>Capacity *</b>	9000 Gallons (34000 liters)	9000 Gallons (34,000 liters)
<b>Flow Rate *</b>	1.67 GPM (6.32 LPM)	1.67 GPM (6.32 LPM)
<b>Maximum Feed Pressure</b>	125 psi (8.6 bar)	125 psi (8.6 bar)
<b>Minimum Feed Pressure</b>	20 psi (1.4 bar)	20 psi (1.4 bar)
<b>Maximum Feed Temperature</b>	100 F (38 C)	100 F (38 C)
<b>Minimum Feed Temperature</b>	40 F (5 C)	40 F (5 C)
<b>Filter Dimensions</b>	15.125 H" x 3 D" (38.42 cm x 7.62 cm)	15.125 H" x 3 D" (38.42 cm x 7.62 cm)
<b>Dry Weight lbs. (kg)</b>	1.6 lbs (.73)	1.6 lbs (.73)

***\*Capacity and flow rate are based on 1.67 gallons per minute (6.32 liters per minute). These cartridges are tested and certified by NSF against ANSI/NSF Standard 42 for material requirements.***

***Nimbus Water International, Sea Lion Place, Suite 103, Carlsbad, CA 92008 USA***

***Website:           www.nimbuswaterintl.com***  
***Phone:             760.603.0867***  
***Fax:                760.603.0868***  
***Email:             salesinfo@nimbuswaterintl.com***